

3300 SERIES PRODUCT TECHNICAL DATA SHEET

OEM: 3323-2L1-63B
AFTERMARKET: 3323-2L1-63B-B

APPLICATION: Agricultural and Chemical Spray application intermittent duty use. This pump is not listed for potable water use.



PUMP DESIGN:

Type: 3 Chamber Positive Displacement Diaphragm
Maximum Flow: 2.2 GPM [7.6 LPM]
Fluid Ports: 3/4" Quick Attach Female
Liquid: 140 F [60 C] MAX
Dry Prime: 8 feet [2.4M]
Run Dry: Yes
Pressure Setting: 200 PSI [13.8 Bar]
Control: Bypass
Label: Remco Label, Part #, Specs, Serial #, MFG date

Electrical:

Motor: 12 VDC Permanent Magnet, Intermittent Duty
Voltage Range: 11.5 VDC – 14.5 VDC
Max Amps: 12 Amps
Leads: 14 AWG, 6" [15cm], 2 Pin Connector
Fuse: 12.5 Amp recommended
Control: Bypass
Max Temp: 180 F [82 C]
IP Rating: IP65



MATERIALS OF CONSTRUCTION:

Pumphead: Polypropylene
Diaphragm: Santoprene
Valves: Viton
Valve housing: Polypropylene
Hardware: Zinc plated screws

AGENCY APPROVALS:

CE, RoHs, UL

SHIPPING INFORMATION:

Net Weight: 5 lbs [2.27]
Carton Qty: 6 units
Carton Weight: 32 lbs [14.51]
Carton Size: 6" x 22" x 17.75"

PSI	GPM	BAR	LPM	Amperage
0	2.20	0.00	8.33	2.65
20	1.95	1.38	7.38	4.40
40	1.60	2.76	6.06	5.80
60	1.45	4.14	5.49	6.40
80	1.35	5.52	5.11	6.90
100	1.00	6.90	3.79	7.70
120	0.95	8.28	3.60	8.10
140	0.75	9.66	2.84	8.90
160	0.60	11.03	2.27	9.50
180	0.55	12.41	2.08	10.50
200	0.45	13.79	1.70	11.50

HEAT RISE 3323-2L1-63B

