

FATBOY SERIES PRODUCT TECHNICAL DATA SHEET

OEM: 5518-1E1-69C
 AFTERMARKET: 5518-1E1-69C-B (Includes Fittings)

APPLICATION: Agricultural Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



PUMP DESIGN:

Type: 5 chamber, positive displacement diaphragm
 Maximum Flow: 7.0 GPM [26.05 LPM]
 Fluid Ports: 3/4" Quick Attach Female
 Liquid Temp: 140 F [50 C]
 Prime: 14 feet [4.2M]
 Run Dry: Yes
 Pressure Setting: 60 PSI [4.1Bar]
 Label: Remco Label, Part #, Specs, Serial #, MFG date

ELECTRICAL:

Motor: 110/120 VAC Permanent Magnet, Intermittent duty, Sealed motor
 Voltage Range: 110 VAC – 120 VAC
 Max Amps: 5 Amps
 Leads: 6' [1.82m] 3 prong plug and cord
 Fuse: 7.5 Amp Recommended
 Control: Pressure switch
 Max Temp: 180 F [82 C]
 IP Rating: IP65

MATERIALS OF CONSTRUCTION:

Housings: Polypropylene
 Valves: Viton
 Diaphragm: Santoprene
 Base: Welded
 Hardware: Zinc plated screws

AGENCY APPROVALS:

CE, RoHs

SHIPPING INFORMATION:

Net Weight: 8 lbs
 Carton Qty: 4
 Carton Weight: 42 lbs
 Carton Size: 6" x 22" x 17.75"

PSI	GPM	BAR	LPM	Amperage
0	7.00	0.00	26.50	1.00
10	6.80	0.69	25.74	1.00
20	6.45	1.38	24.42	1.50
30	5.90	2.07	22.33	2.00
40	5.50	2.76	20.82	2.50
50	4.95	3.45	18.74	2.50
60	4.40	4.14	16.66	2.50

HEAT RISE 5518-1E1-69C

