

5500 SERIES PRODUCT TECHNICAL DATA SHEET

OEM: 5536-1E1-731B
AFTERMARKET: 5536-1E1-731B-B

APPLICATION: Agricultural Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



PUMP DESIGN:

Type: 5 chamber, positive displacement diaphragm
Maximum Flow: 4.0 GPM [15.14 LPM]
Fluid Ports: 1/2" FNPT
Liquid Temp: 140 F [50 C]
Prime: 14 feet [4.2M]
Run Dry: Yes
Pressure Setting: 60 PSI [4.1Bar]
Label: Remco Label, Part #, Specs, Serial #, MFG date

ELECTRICAL:

Motor: 24 VDC Permanent Magnet, Intermittent duty, Sealed motor
Voltage Range: 23 VDC – 27.5 VDC
Max Amps: 8 Amps Max at 60 PSI [4.1 Bar]
Leads: 14 AWG, 5.5" [13.9cm], 2 pin connector
Fuse: 10 Amp Recommended
Control: Pressure switch
Max Temp: 180 F [82 C]
IP Rating: IP65

MATERIALS OF CONSTRUCTION:

Housings: Polypropylene
Valves: Viton
Diaphragm: Santoprene
Base: Welded
Hardware: Zinc plated screws

AGENCY APPROVALS:

CE, RoHs

SHIPPING INFORMATION:

Net Weight: 8 lbs [3.63 kg]
Carton Qty: 6 units
Carton Weight: 42 lbs [19.05 kg]
Carton Size: 6" x 22" x 17.75"



PSI	GPM	BAR	LPM	Amperage
0	4.10	0.00	15.52	3.50
10	4.00	0.69	15.14	4.25
20	3.75	1.38	14.20	4.50
30	3.40	2.07	12.87	5.50
40	3.05	2.76	11.55	6.25
50	2.75	3.45	10.41	7.00
60	2.45	4.14	9.27	8.00

HEAT RISE 5536-1E1-731B

