



## POWER RV™

Fresh Water Applications • General Industrial Use • RV and Coach Water Pumps

### PUMP FEATURES

- Made in the USA
- Professional Grade
- Additional voltage options
- FLO IQ technology inside
- Low amp draw
- Noise dampening rubber base
- Dual control to eliminate cycling
- Thermal protection

### PUMP PERFORMANCE (Performance may vary)

3200 Series			
PSI	GPM	LPM	AMPS
OPEN	3.20	12.11	4.10
10	2.90	10.98	5.30
20	2.60	9.84	6.20
30	2.40	9.08	7.30
40	2.10	7.95	8.10
50	1.90	7.19	8.80
60	1.70	6.44	9.50
70	1.50	5.68	10.00
80	1.30	4.92	10.30



## TECHNICAL INFORMATION

**TYPE**  
3 chamber variable speed diaphragm pump. Self priming and capable of being run dry

**TEMPERATURE LIMITS**  
Thermal protector shut down if heat rises above 180°F (82°C).

**LEADS**  
18 AWG, 7" stripped leads

**MAX PRESSURE**  
45 PSI (3.1 BAR)

**LIQUID TEMPERATURE**  
140°F (60°C) Max

**PRIMING CAPABILITIES**  
10ft (3m)

**PRESSURE CONTROL**  
Demand

## CERTIFICATIONS



## PUMP CONFIGURATIONS *(Contact us for additional configurations)*

### 3200 STANDARD

Item Number	Flow	Controls	Pressure	Valves	Diaphragm	Ports	Voltage
3214-1C4-82L	3.2 GPM (12.11 LPM)	DEMAND	45 PSI (3.1 BAR)	EPDM	SANTOPRENE	3/4" QUICK ATTACH	12 VDC

### 24 VDC

Item Number	Flow	Controls	Pressure	Valves	Diaphragm	Ports	Voltage
5518-1E1-94A	3.2 GPM (12.11 LPM)	DEMAND	45 PSI (3.1 BAR)	EPDM	SANTOPRENE	3/4" QUICK ATTACH	24 VDC

### 115 VAC

Item Number	Flow	Controls	Pressure	Valves	Diaphragm	Ports	Voltage
5518-1E1-94A	3.2 GPM (12.11 LPM)	DEMAND	45 PSI (3.1 BAR)	EPDM	SANTOPRENE	3/4" QUICK ATTACH	115 VAC